```
FOR COATINGS, RESINS AND RELATED MATERIALS
            SECTION I
************
Manufacturers Name SHEFFIELD BRONZE PAINT CORP
                                        Emergency Phone No.
Street Address 17814 S.WATERLOO RD. (216) 481-8330
City, State, Zip CLEVELAND, OHIO 44119 TRANSPORTATION EMERGENCIES: CHEMTREC
                                    (800) 424-9300 CONTINENTAL U.S.
PRODUCT NUMBER: 11-503
                                     (202) 483-7616 (COLLECT) FROM
PRODUCT NAME: VAN DYKE BR. -9 TINTSALL
                                                ALASKA & HAWAII
PRODUCT CLASS: UNIVERSAL TINTING COLOR
*******************
                 SECTION II - HAZARDOUS INGREDIENTS
*****************
                 * CAS NUMBER*PERCENT* TLV
                                                  VAPOR PRESSURE
                     * * PPM MG/M3* LEL * MM/HG
********************
: IRON OXIDE : 51274-00-1 : 4.8 :
                                     :
                : 1309-37-1 : 3.0 :
: IRON OXIDE
: IRON OXIDE : 12227-89-3 : 10.0 :
NON-IONIC BIODEGRADABLE
                68154-97-2 : 13.5 :
SURFACTANT
**DIACETONE ALCOHOL 123-42-2 : 13.5 : 50 : 240 : 1.8 : .95 : CALCIUM CARBONATE : 471-34-1 : 54.7 : : : :
                : LESS THAN : 1.0 :
: ADDITIVES
*ALL INGREDIENTS ARE LISTED ON THE EPA/TSCA INVENTORY
*SARA TITLE 111 SECTION 313 REPORTING FOR SUPERFUND AMENDMENTS
            SECTION III - PHYSICAL DATA
**********************
Boiling Range: 337dgr F Vapor Density: HEAVIER THAN AIR
Evaporation Rate: SLOWER than Butyl Acetate V.O.C.:2.24#/GALLON; 270 GRAMS/LI
Percent Volatile by VOLUME: 27.4
                           Weight per GALLON: 16.0 LBS.
Percent Volatile by WEIGHT: 14.0
*****************
                 SECTION IV - FIRE and EXPLOSION DATA
**************
DOT CATEGORY: COMBUSTIBLE FLASH POINT (SETA) - 138 Degrees F.
EXTINGUISHING MEDIA: CO-2, DRY CHEMICAL, FOAM, FOG
UNUSUAL FIRE AND EXPLOSION HAZARDS: HANDLE AS A COMBUSTIBLE LIQUID
SPECIAL FIRE FIGHTING PROCEDURES: NONE
*********************
                SECTION V - HEALTH HAZARD DATA
*******************
THRESHOLD LIMIT VALUE: 50ppm OR 240MG/M3 TWA (8 hr. Workday)
EFFECTS OF OVEREXPOSURE: BREATHING VAPOR IS IRRITATING TO EYES, NOSE AND
THROAT. CONTACT WITH EYES AND SKIN CAN CAUSE DRYNESS & IRRITATION
EMERGENCY AND FIRST AID PROCEDURES: Flush eyes immediately with large amounts
of water. Wash skin areas with water. Remove to fresh air. IF INGESTED: If
patient is conscious can swallow, give two glasses of water (16 oz.), induce
vomiting as directed by medical personnel. Do not induce vomiting or give any-
```

thing by mouth to an unconscious or convulsing person.

Get medical attention immediately.

MATERIAL SAFETY DATA SHEETS

DATE: AUGUST, 2002

: PAGE TWO - VAN DYKE BROWN 9 TINTSALL #11-503
SECTION VI - REACTIVITY DATA

STABILITY: STABLE CONDITIONS AND MATERIALS TO AVOID: HIGH HEAT, FLAME, STRONG OXIDIZING AGENTS, NITRIC ACID AND STRONG BASES. HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE AND/OR CARBON DIOXIDE AND
UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION. HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
SECTION VII - SPILL OR LEAK PROCEDURES ************************************
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Remove all sources of ignition, ventilate, avoid breathing vapors.
Remove with INERT ABSORBENT(sand, earth, sawdust etc.) WEAR SUITABLE PROTECTIVE EQUIPMENT.
WASTE DISPOSAL METHOD:
DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, and LOCAL REGULATIONS. AT VERY LOW CONCENTRATIONS IN WATER, THIS PRODUCT IS BIODEGRADABLE IN A BIOLOGICAL WASTE WATER TREATMENT PLANT.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NIOSH APPROVED AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS. IN AREAS OF HIGH VAPOR CONCENTRATION, USE AN ATMOSPHERE SUPPLYING
BREATHING APPARATUS.
VENTILATION: MECHANICAL VENTILATION EQUAL TO OUTDOORS
PROTECTIVE GLOVES: RECOMMENDED FOR PROLONGED OR REPEATED CONTACT
EYE PROTECTION: SAFETY GLASSES WITH UNPERFORATED SIDESHIELDS
OTHER PROTECTIVE EQUIPMENT: SAFETY SHOWERS, CHEMICAL RESISTANT CLOTHING ************************************
SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: HANDLE AS A COMBUSTIBLE LIQUID. STORE IN A COOL DRY PLACE. USE ADEQUATE VENTILATION EQUIVALENT TO THE OUTDOORS
OTHER PRECAUTIONS: KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME. SMOKING SHOULD
BE PROHIBITED WHERE USED. KEEP OUT OF REACH OF CHILDREN.

SECTION X - HAZARDOUS MATERIAL IDENTIFICATION

LISTED IN THIS SECTION IS NPCA-HMIS CLASSIFICATION FOR THIS PRODUCT
Health : 3 :
Flammability : 2 :
Reactivity : 0 :
Personal Protection: B :

Information above pertains to this product as currently formulated. Addition of
other additives may alter the Composition and Hazards. WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED AND ASSUME NO LIABILITY WITH USE OF THIS INFORMATION.